

SWING CHECK VALVE

DESIGN	ASME B16.34 ASME III - ASME PV CODE 8 2014/68/UE P.E.D. ISO 15848 FUGITIVE EMISSIONS	
FACE TO FACE	ASME B16.10	
SERIES	CF CF / M CF / IM / AT	
CLASS	ANSI 150-300-600-900	
SERVICE	ON - OFF	
ENDS	FLANGED BUTTWELD	
SEAL SEATS TYPE	Metal	
ENDS COUPLING	ASME B16.5 - ASME B16.47 - ASME B16.25	
SIZE	from 6 inches to 30 inches	
TESTING	FCI 70.2 - IEC 534 - API 6D - API 598 - UNI EN 12266 Special testing on request	
COUPLING TO ACTUATORS	ISO 5211 - Other on request	
STANDARD MATERIALS	BODY	WCB - WC6 - WC9 Other on request
	CLAPET	CA6NM - AISI 410 Other on request
	STEM	AISI 316 - AISI 420B - NITRONIC 50 - Other on request
	SEAL SEAT	AISI 316 - AISI 410 WITH STELLITE
	BUSHING	D.U. - TG30 - TG61F
	STEM SEAL	CARBOGRAPHITE+NBR / VITON / SILICONE KALREX PTFE PACKING GRAPHITE PACKING