

# MODULAR SYSTEM

## FOR GAS FILTRATION

<b>DESIGN</b>	ASME B16.34 ASME III - ASME PV CODE 8 2014/68/UE P.E.D. SIL IEC 61508 ISO 15848 FUGITIVE EMISSIONS			
<b>EXECUTION</b>	<b>SERIES</b>	<b>SIZE</b>	<b>MAX PRESSURE</b>	<b>MAX TEMP</b>
<b>2P MODULE</b>	BLVF	20-25-40	120 BAR	150 °C
	BLVF-TEF-HC-MF	20-25-40	160 BAR	180 °C
	BLVF-TEF-HC-MF/HT	20-25-40	135 BAR	260 °C
<b>3P MODULE</b>	BLVF	20-25-40	120 BAR	150 °C
	BLVF-HC	20-25	120 BAR	150 °C
	BLVF-HC-MF	20-25-40	120 BAR	180 °C
	BLVF-TEF-HC-MF	20-25-40	120 BAR	180 °C
	BLVF-TEF-HC-MF/HT	20-25-40	110 BAR	260 °C
<b>5P MODULE</b>	BLVF	20-25-40	360 BAR	150 °C
	BLVF-HC	20-25	360 BAR	150 °C
	BLVF-HC-MF	20-25-40	360 BAR	180 °C
	BLVF-TEF-HC-MF	20-25-40	360 BAR	180 °C
	BLVF-TEF-HC-MF/HT	20-25-40	320 BAR	260 °C
<b>ENDS CONNECTION</b>	<ul style="list-style-type: none"> <li>• WELDING NECK SIZE 20-25-40 SCH. 80S - 160S ACC. TO ASME B16.25 - ASME B16.5</li> <li>• NPT F SIZE ¾" - 1" ACC. TO ANSI B1.20.1, lateral or frontal connection</li> <li>• Other special connection on request</li> </ul>			
<b>TESTING</b>	MSS-SP61 - FCI 70.2 Special testing on request			
<b>STANDARD MATERIALS</b>	BODIES	ASTMA182 F 316L - ASTMA182 F51 ASTMA564-630 - 17.4.PH ASTMA494 CW 6MC other on request		
	TRIM	WCB + ENP - A105 + ENP - CF8 - CF8M - DULPLEX - CA6NM Other on request		
	SEAL SEAT	PTFE / FILLED - PTFE		
	GASKETS	VITON - FR58/90 EX-PROOF - AF 69/90 RED SILICON A90H - KALREX - AISI 316+GRAPHITE		